

2026 SUMMIT® ADRENALINE®

An excellent deep-snow machine for any rider.

// PACKAGE HIGHLIGHTS

- tMotion™ X® rear suspension
- LED headlights
- Pilot™ DS 3 skis
- RAS™ 3 front suspension with 930 mm [36 in.] ski stance



ROTAX® ENGINE

	850 E-TEC®	600R E-TEC®
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, two-stroke, eRAVE™
Cylinders – Displacement	2 – 849 cc	2 – 599.4 cc
Bore – Stroke	82 x 80.4 mm	72.3 x 73 mm
Fuel System	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection
Fuel type – Octane	Premium unleaded – 95	
Fuel tank (L)	36	
Oil tank capacity (L)	3.4	

POWERTRAIN

	pDrive™ with clickers QRS Vent Plus	pDrive™ with clickers QRS Vent
Drive clutch		
Driven clutch		
Drive sprocket pitch	73 mm [146 in.] 89 mm [154 in.]	


DRY WEIGHT

	205 kg [146 in.] 203 kg [154 in.]	200 kg [146 in.] 198 kg [154 in.]
Dry weight		

DIMENSIONS

Vehicle overall length	3,208 mm [146 in.] 3,318 mm [154 in.]
Vehicle overall width	1,073 mm [adjustable]
Vehicle overall height	1,395 mm
Ski stance	930 mm [adjustable]
Available tracks (in.)	PowderMax¹ with FlexEdge™: 146 x 16 x 2.5
(Length x width x profile)	PowderMax¹ Light with FlexEdge™: 154 x 16 x 2.5

COLOR

Catalyst Grey 

SUSPENSION

Front suspension	RAS 3
Front shock	KYB 36
Front suspension travel	215 mm
Rear suspension	tMotion X
Center shock	KYB 36
Rear shock	KYB 36
Rear suspension travel	264 mm

FEATURES

Platform	REV® Gen5
Headlights	LED
Skis	Pilot DS 3
Seating	Deep snow
Handlebar	Tapered with J-hooks / Grab handle
Riser block height	120 mm
Starter	Electric Starter
Reverse	RER™
Brake system	Brembo
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	No
Runner (in.) – Carbide (in.)	3/8 square – 4
Bumpers (front/rear)	Standard / Standard

ski-doo

A BRP BRAND

