## 2026

## MXZ° X-RS° WITH COMPETITION PACKAGE

Yes it's an ultra-fast laker, but before anything else it's the ultimate ditch banger. Powerful, lightweight and highly capable with race-ready features.

## // WHAT'S NEW

• Mineral Blue Premium color

## // PACKAGE HIGHLIGHTS

- Pilot™ RX skis
- KYB Pro 40 Kashima coated shocks with Integral Base Valve (600R E-TEC® only)
- Launch Mode and E-TEC® SHOT™ starter (850 E-TEC® Turbo R only)
- KYB Pro 40 Kashima coated front shocks
- 10.25 in. touchscreen display with BRP Connect and built-in GPS
- rMotion™ X Competition rear suspension
- RS running boards



ROTAX® ENGINE	850 E-TEC® TURBO R	600R E-TEC®
Engine details	Liquid-cooled, two-stroke, turbocharged, Water Injection System, eRAVE™	Liquid-cooled, two-stroke, eRAVE™
Cylinders - Displacement	2 - 849 cc	2 - 599.4 cc
Bore – Stroke	82 x 80.4 mm	72.3 x 73 mm
Fuel System	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection
Fuel type – Octane	Premium unleaded - 95	
Fuel tank (L)	36	
Oil tank capacity (L)	3.4	
POWERTRAIN		
Drive clutch Driven clutch	pDrive™ with clickers QRS Vent Plus	pDrive™ with clickers QRS
Drive sprocket pitch	73 mm	
DRY WEIGHT		
Dry weight	237 kg	220 kg
DIMENSIONS		
Vehicle overall length	3,038 mm	
Vehicle overall width	1,211 mm (adjustable)	
Vehicle overall height	1,267 mm	
Ski stance	1,090 mm (adjustable)	
Available tracks (in.) (Length x width x profile)	RipSaw† II 2-ply: 137 x 15 x 1.25	Cobra: 137 x 15 x 1.6

COLOR Mineral Blue		
Mineral Blue		
SUSPENSION		
Front suspension	RAS RX	
Front shock	KYB PRO 40 Integral R Kashima (600R E-TEC) KYB PRO 40 EA-3 Kashima (850 E-TEC Turbo R)	
Front suspension travel	279 mm	
Rear suspension	rMotion X Competition	
Center shock	KYB PRO 40 Integral Kashima coated (600R E-TEC) KYB PRO 40 EA-3 (850 E-TEC Turbo R)	
Rear shock	KYB PRO 40 EA-3 (850 E-TEC Turbo R) KYB PRO 40 Integral Kashima (600R E-TEC)	
Rear suspension travel	292 mm	
FEATURES		
Platform	REV® Gen5	
Headlights	Premium LED	
Skis	Pilot RX	
Seating	Trail narrow	
Handlebar	Standard with J-hooks / Transparen handguards	
Riser block height	90 mm	
Starter	850 E-TEC Turbo R: SHOT 600R E-TEC: Manual Starter	
Reverse	RER™	
Brake system	Brembo 4-piston with adjustable leve	
Heated throttle lever/grips	Standard	
Gauge type	10.25 in. touchscreen display (850 Turbo R) 7.2 in. digital display (600R)	
Windshield	Ultra-low	
Runner (in.) – Carbide (in.)	3/8 square - 4	
Bumpers (front/rear)	Standard / Standard	



