

2027 COMMANDER XT



■ Triple Black
■ Dolomite Grey

PACKAGE HIGHLIGHTS

700	1000R
• 7.6 in. digital display with keypad • Can-Am LED signature • 28 in. XPS Trail King tires • 14 in. cast-aluminum wheels • XT front bumper • 4,500 lb (2,041 kg) winch with synthetic cable • Full hard roof	

ENGINES	700	1000R
Type	52 hp / 42 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid cooled	100 hp, Rotax® 976 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary CVT with engine braking and Electronic Drive Belt Protection L / H / N / R / P	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Visco-Lok¹ QE auto-locking front differential	Selectable Turf Mode / 2WD / 4WD auto-locking QE front differential
Driving Assistance	CVT Engine Braking SPORT / ECO™ modes	
Power Steering	Dynamic Power Steering (DPS)	

SUSPENSIONS

Front Suspension	Double A-arm with sway bar / 12.5 in. (31.8 cm) suspension travel	Arched double A-arm with sway bar / 15 in. (38.1 cm) travel
Front Shocks	Twin tube gas charged shocks	
Rear Suspension	TTA with sway bar / 13 in. (33 cm) suspension travel	Arched TTA with sway bar / 15 in. (38.1 cm) travel
Rear Shocks	Twin tube gas charged shocks	

TIRES & WHEELS

Front / Rear Tires	XPS Trail King 28 x 9/11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Twin piston caliper (32 mm) / 220 mm discs
Rear	Twin piston caliper (28 mm) / 220 mm discs

DIMENSIONS & CAPACITIES

	700	1000R
Estimated Dry Weight	1,594 lb (723.4 kg)	1,694 lb (768.8 kg)
Cage	Profiled cage ROPS approved	
L x W x H	130 x 64 x 74 in. (330.2 x 162.6 x 188 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	13 in. (33 cm)	
Cargo Box Dimensions	130 x 62 x 74 in. (330.2 x 157.5 x 188 cm)	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)	
Power Tilt Bed	Manual tilt	
Storage Capacity	Total: 7.3 gal (27.6 L)	
Towing Capacity	2,000 lb (907.2 kg)	
Payload Capacity	1,030 lb (467.2 kg)	
Fuel Capacity	10 gal (38 L)	
Person Capacity	2	

FEATURES

Gauge	7.6 in. display
Battery	18 Ah (270 CCA)
Magneto	650 watts
Instrumentation	DC outlet (10-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	Front lighting output 110-W LED signature LED taillights
Winch	4,500 lb (2,041 kg) winch with synthetic cable
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors • Full heavy-duty HMW plastic skid plate • Mudguards • XT front bumper • Full hard roof • Lower front mudflap
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP Limited warranty
Extended Service Terms	B.E.S.T. term available up to 48 months



© 2026 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

